

## DLW

### "DLW" SERIES AUTOMATED WEIGHING FOR +/- WEIGHT CHECKING



Compact, reliable and accurate +/- weight checking systems. Particularly suitable to be integrated with production and/or shipping conveyor lines for a weight check which guarantees the quality and quantity of the outgoing products. Static or dynamic functioning modes. MID R51 – Start & stop - approvable.

Working in cooperation with:

*AHNE TECH STAFF*  
-- MUSCAT  
[alhinaoman@gmail.com](mailto:alhinaoman@gmail.com)

**The best solution  
for advanced industrial  
applications**

## WEIGHT AND CHECK FUNCTIONS

- Static or dynamic weighing of packs, both automatically as well as semiautomatically with the operator.
- Management of the cadence belt, for optimising the number of packs per minute weighed by the instrument (cadence belt not included), through cadence photo cell (optional).
- Setting of the density coefficient for each article, for weighing in ml.
- Programmable alarm enabling and tolerance indication time.
- Tolerance check:
  - Upon target, through article database, with setting of 3 tolerance thresholds, for the physical division of the packs into 7 different groups.
  - Upon programmable weight thresholds (min/max), with article database.
  - Upon weight thresholds (min/max), with quick entry function.
- Printout with each executed weigh with eventual automatic storage in the alibi memory.
- Automatic printout and clearing of the partial total after a programmable number of weighs.
- Static or dynamic automatic zero function of the belt (up to 2% of the capacity) after a programmable number of weighs.
- Management of the automatic expulsion through its specific relay contact (expeller not included in the supply), or halt of the belts for manual expulsion or weight correction.
- Possibility of connection to RS485 network or ethernet.
- Programmable preset tare and enabling delay of the expeller for each article.
- Automatic calculation of the weigh time and pack positioning, for optimising the functioning of the system.
- Database of 1000 articles, with programmable alphanumeric description, density, targets, tolerance thresholds, and preset tare for each article.
- Selection of the article through bar code reading.
- Advanced bar code management, with the possibility of storing, processing, and printing 5 different codes.
- Configuration and calibration of the instrument through the tool on the PC.
- Report with date and time of cycle beginning and end with statistics of the checks and/or activities, standard deviation of the executed weighs, and totals by class and/or article.
- Possibility of connection to a control light.

## E-CHECKTOOL: Quick programming of the indicator

- Programme on PC for optimising the weighing cycle; it's possible to monitor the status of the inputs and outputs of the instrument, transmit serial commands for managing the automation, quickly modify the instrument parameters, graphically view and process the weighs in order to obtain the best weighing results.

## I/O SECTION

- 8 digital inputs and 16 outputs for command switch on the line.
- 1 RS232/C serial port for managing a built-in printer, or labeller.
- 1 RS232/C bidirectional port for data exchange with PC/PLC.
- 1 RS485 bidirectional port for network connection with other devices and communication with PC/PLC.
- 1 keyboard emulation input for connection to PC keyboard or bar code reader.

## MAIN CERTIFICATIONS

- EU Type Examination Certificate (45501:2015)
- OIML R76
- OIML R51 - MID for START/STOP automated weighing

## TECHNICAL SPECIFICATION

- Bearing structure and frame in painted steel.
- Loading platform with motor driven conveyor mat, with adjustable height and direction.
- Rear handling and positioning wheels, and adjustment and fixing feet.
- Adjustable weighing belt speed: from 10 to 27m/min, max 27 PCS/min (higher speed upon price estimate).
- Electromechanical automation for belt command and 6 auxiliary relays (up to 5A 220V).
- Fitted with pack presence and weigh end photo cells (for dynamic weighing), with adjustable reading distance.
- Overall switch, emergency button, start/restart button, optical/acoustic alarm (in painted steel versions).
- Easy to consult backlit LCD graphic display, with clear visualisation of the weight and automation status; selection of the language from the menu.
- Selection of the data (totals, progressives, weight...) shown on the graphic LCD display.
- Waterproof 25 key numerical-functional keyboard, which allows to easily enter the target, alphanumeric texts, codes, etc. IP65 protection degree of the front panel, against dust and sprays.
- Keyboard functions completely configurable according to one's requirements.
- Real time clock and permanent memory data.
- Built-in alibi memory, for CE-M transmission of the weight data to the PC or printer.
- 240Vac 50Hz power supply.

### PACKAGING IS INCLUDED IN THE PRICE

for the complete protection against scratches and bumps during transportation. The weighing belt is shipped inside a sturdy wooden case which is custom made.

This special service is included in the price of the product.

## VERSIONS

### Available versions

Codice	l x w x h (mm)	Max (kg)	d (g)
DLW5080	800 x 500 x 450..850	6, 15, 30	2, 5, 10
DLW6510	1000 x 650 x 450..850	15, 30	5, 10

#### NOTE:



- ATTENTION: The order of the DLW is possible only upon verification of the system's data, executed by our technicians when the filled out DataRequest\_DLW module downloadable up here is sent.

- The capacity and division must be specified in the module for the verification of the feasibility, consequently to the requested features.



www.diniargeo.com



“YOUR WORLDWIDE PARTNER FOR WEIGHING,,”

DINI ARGEO  
FRANCE sarl  
Nogent-sur-Marne

DINI ARGEO  
GMBH  
Sinsheim - Germany

DINI ARGEO  
UK Ltd  
Taunton - United Kingdom

DINI ARGEO WEIGHING  
INSTRUMENTS Ltd  
Shanghai - China

DINI ARGEO  
WEIGHBRIDGES  
Calto (RO) – Italy



HEAD OFFICE  
Via Della Fisica, 20  
41042 Spezzano di Fiorano Modena - Italy



**AHNE TECH STAFF**  
 -- MUSCAT  
 alhinaoman@gmail.com  
 SALES AND TECHNICAL ASSISTANCE SERVICE

All the specifications and images can be subject to variations and upgrades without prior notice.