

LCCB

"LCCB": CABLE for CONNECTION TO LOAD CELLS



Shielded cable for connection of weight indicators to load cells or junction boxes.

**The best solution
for advanced industrial
applications**

LCCB cable features

- Type: 6 x 0,25 mm².
- Built-in shielding for protection from disturbances.

<u>Dini Argeo standard of colour codes</u>	
<i>Colour</i>	<i>Function</i>
YELLOW	OUTPUT -
PINK	OUTPUT +
GREEN	SENSE +
WHITE	SENSE -
BROWN	INPUT +
GREY	INPUT -

LCCBM cable features

- Indicated for applications with moving cables.
- Type: 4 x 0,34 mm².
- Built-in shielding for protection from disturbances.

<u>Dini Argeo standard of colour codes</u>	
<i>Colour</i>	<i>Function</i>
YELLOW	OUTPUT -
GREEN	OUTPUT +
WHITE	INPUT -
BROWN	INPUT +

DETAIL 1



LCCBM: shielded 4-pole cable for load cells.



“YOUR WORLDWIDE PARTNER FOR WEIGHING,”

**DINI ARGEO
FRANCE sarl**
France

**DINI ARGEO
GMBH**
Germany

**DINI ARGEO
UK Ltd**
United Kingdom

**DINI ARGEO WEIGHING
INSTRUMENTS Ltd**
China

**DINI ARGEO
OCEANIA**
Australia



COMPANY HEADQUARTERS

Via Della Fisica, 20
41042 Spezzano di Fiorano Modena • Italy
Tel. +39.0536 843418

SERVICE ASSISTANCE

Via Dell'Elettronica, 15
41042 Spezzano di Fiorano Modena • Italy
Tel. +39.0536 921784

SALES AND TECHNICAL ASSISTANCE SERVICE