

RSBT

RSBT DOUBLE SHEAR BEAM LOAD CELLS



Double shear beam load cells particularly suitable for weighing weighbridges, dosage systems, tanks, silos, etc., complete with support and oscillating spherical joint. CE-M approved.

CAPACITIES (kg): 25000, 30000, 40000.

OIML R60. C3 precision class.

Nickel-plated steel. **IP68** protection.

The best solution
for advanced industrial
applications

MAIN FEATURES

- C3 PRECISION CLASS;
- EXECUTED IN NICKEL-PLATED STEEL WITH LASER SOLDERINGS;
- HIGH PRECISION AND LINEARITY ALSO WITH NON PERPENDICULAR LOADS;
- OPTIMISED FOR PARALLEL CONNECTION;
- IP68 PROTECTION DEGREE;
- CAPACITY FROM 25000 TO 40000kg;
- SHIELDED TEFLON CONNECTION CABLE;
- TEST CERTIFICATE AVAILABLE UPON REQUEST.

TECHNICAL FEATURES

- Minimum verification interval: $V_{min} = E_{Max} / 10.000$;
- Maximum number of load cell divisions: $n_{LC}=3000$ (C3);
- Full Scale Output: $2mV/V \pm 0,2\%$;
- Temperature effect on full scale output: $0,0014\%FS/^{\circ}C$;
- Temperature effect on the zero: $\pm 0,0017\%FS/^{\circ}C$;
- Compensated temperature range: $-10^{\circ}C/+40^{\circ}C$;
- Operating temperature range: $-35^{\circ}C/+65^{\circ}C$;
- Creep error after 30 minutes: $0,02\%$ F.S.;
- Excitation voltage: from 5 to 18 VDC;
- Input Resistance: 750 Ohm;
- Output Resistance: 700 ± 7 Ohm;
- Zero Balance: $\pm 1,5\%$ F.S.;
- Insulation resistance > 5000 MOhm;
- Safe overload $> 150\%$ F.S.;
- Maximum overload 300% F.S.;
- 4-wire shielded cable, 15m long, 6mm diameter.




ATEX VERSION

- The CCATEX certificate makes the load cell suitable for use in hazardous areas with protection methods according to:
ATEX II 1G Ex ia IIC T6 (Ta $-20 \div +40^{\circ}C$) TX (Ta $-20 \div +65^{\circ}C$) Ga
ATEX II 1D Ex ta IIIC TX $^{\circ}C$ (Ta $-20 \div +40^{\circ}C$) TX $^{\circ}C$ (Ta $-20 \div +65^{\circ}C$) Da IP65.
The certificate includes the manual and the ATEX CE conformity declaration (available in EN, DE, FR, and IT).
- IMPORTANT: the certificate refers to the single load cell. For systems with more load cells, it is necessary to order one certificate for each load cell.

<u>Wiring Code</u>	
<u>Colour</u>	<u>Function</u>
--	SHIELD
GREEN	OUTPUT +
RED	INPUT +
WHITE	OUTPUT -
BLACK	INPUT -

VERSIONS

Available versions

Code	Max (kg)
RSBT25C3 	25000
RSBT30C3 	30000
RSBT40C3 	40000



www.diniargeo.com



“YOUR WORLDWIDE PARTNER FOR WEIGHING”

DINI ARGEO
FRANCE sarl
France

DINI ARGEO
GMBH
Germany

DINI ARGEO
UK Ltd
United Kingdom

DINI ARGEO WEIGHING
INSTRUMENTS Ltd
China

DINI ARGEO
OCEANIA
Australia



COMPANY HEADQUARTERS

Via Della Fisica, 20
41042 Spezzano di Fiorano Modena • Italy
Tel. +39.0536 843418

SERVICE ASSISTANCE

Via Dell'Elettronica, 15
41042 Spezzano di Fiorano Modena • Italy
Tel. +39.0536 921784

SALES AND TECHNICAL ASSISTANCE SERVICE

All the specifications and images can be subject to variations and upgrades without prior notice.