

# ETHD

## "ETHD": ETHERNET INTERFACE FOR INDICATORS



Small size, excellent signal quality, support of the most common network protocols are just a few features of this product, which allows for a network connection of any scale or weighing system to the company's computer system through the RJ45 connector; it' easy to install and it's fitted with a cable for the connection to the indicators

The module does not exclude the use of other Dini Argeo products on the system, such as Control Light, Alibi Memory, attached or external printer.

The best solution for advanced industrial applications

#### **TECHNICAL FEATURES**

- Connection to the mains through the standard RJ45 connector
- Mains interface: 10/100 Base-T
- Supported protocols: TCP, UDP, DHCP, HTTP, ICMP, uPnP, ARP
- Size: Height = 50 mm; Width = 87 mm.
- Visual indications: 2 LEDs
  - Green LED: ON when it is connected to the 10/100 Base-T mains.
  - Yellow LED: ON in the presence of the mains activity.
- Operating temperature: -20°C +85°C
- Power supply: from 5 to 12Vdc
- Max. absorption: 350 mA.

The accessory may be ordered only combined with a suitable weight indicator.

In case of installation in existing systems, it is recommended to consult the manual to verify compatibility with devices in use.

### DETAIL 1

i

1

|  | Status & Configuration     |                        |
|--|----------------------------|------------------------|
| veral<br>tings<br>t 0 (RS232)<br>tings<br>t 1 (RS485)<br>tings |                            |                        |
|  |                            | Miscellaneous Settings |
|  | Home                       | Name                   |
|  | General                    | Firmware Revision      |
|  | Settings                   | IP Address             |
|  | Port 0 (RS232)<br>Settings | MAC Address            |
|  | Port 1 (RS485)<br>Settings | IP Address Selection   |
|  | Password                   | Address Type:          |
|  | seming                     | Static IP Address.     |
|  |                            | Subnet Mask            |
|  |                            | Default Gateway:       |

Programming accessible by the integrated web interface. It does not require any other pc application for the configuration.





DINI ARGEO FRANCE sarl France DINI ARGEO GMBH Germany DINI ARGEO UK Ltd United Kingdom DINI ARGEO WEIGHING INSTRUMENTS Ltd China DINI ARGEO OCEANIA Australia



#### COMPANY HEADQUARTERS

Via Della Fisica, 20 41042 Spezzano di Fiorano Modena - Italy Tel. +39.0536 843418

#### SERVICE ASSISTANCE

Via Dell'Elettronica, 15 41042 Spezzano di Fiorano Modena - Italy Tel. +39.0536 921784 SALES AND TECHNICAL ASSISTANCE SERVICE

.....

All the specifications and images can be subject to variations and upgrades without prior notice.