

# DATASHEET

Maximum quantity of verification units	6000 *
OIML Class	III
Display	7" graphic colour
Protection class	IP 66 / IP 68
USB Interface	1× standard, 1× option (M12 4P)
ETHERNET Interface	1× standard
RS232 Interface	1× standard, 2× option
	1× option
IN/OUT Interface	4 IN 4 OUT standard, 12 IN 12 OUT option
Analog output module (option)	4-20mA, 0-10V
Power consumption max.	25 W
Optional power supply	internal rechargeable battery
Operation time on batteries	max 7h
Maximum increase of signal	19.5 mV
Minimum voltage per verification unit	0.4 $\mu$ V
Maximum voltage per verification unit	3.25 $\mu$ V

Minimum load cell impedance	50 Ω
Maximum load cell impedance	1200 Ω
Load cell excitation voltage	5V DC
Connection of load cells	4 or 6 wires + shield
Operating temperature	-10 ÷ +40 °C
Storage temperature	-10 ÷ +50 °C
Relative humidity	10% ÷ 80% RH no condensation
Keypad	membrane
Material	stainless steel AISI304
Device dimensions	340×231×120 mm
Packaging dimensions	370×310×220 mm
Net weight	4.7 kg
Gross weight	5.5 kg
Max number of platforms	max 2 (1× standard + 1× option)